

AJ Aquacon

installation instructions, application tools

Molding - Suggested method of assembly to cable for Aquacon plugs and cable connecting receptacles is molding. The mold sealing diameter has been designed to use a common mold for both plug and receptacle in a given shell size.

Sealing - In a mated condition, the red visual mating indicator band must be fully concealed by the plug coupling nut to assure a reliable, pressure rated sealed joint. Failure to fully tighten the coupling nut may allow leakage through the main joint seal. The red visual mating indicator is so located that only a full and proper mating of the plug and receptacle will cause the indicator to be fully hidden by the plug coupling nut.

Mounting Surfaces - The integrity of an "O" ring hydrostatic shell is dependent upon the flatness of the surface on which the receptacle is mounted. Surface finishes of 32 microns or less are recommended for "O" ring sealing areas when jam nut or through bulkhead receptacles are mounted.

MOUNTING CUTOUTS	Shell Size	B	R
		+ .010 - .000	+ .010 - .000
<p>Rear mount jam nut</p>	8	.705	.759
	10	.830	.884
	12	.955	1.007
	14	1.080	1.134
	16	1.205	1.259
	18	1.330	1.384
	20	1.455	1.507
	22	1.580	1.634
	24	1.705	1.759

Receptacle "O" Ring Packing Requirements

ARP 568 Uniform Dash Number

Shell Size	Main Joint Seal	Shell to Mounting Surface Seal
		Jam Nut
8	ARP-014	ARP-019
10	ARP-016	ARP-021
12	ARP-018	ARP-023
14	ARP-020	ARP-025
16	ARP-022	ARP-027
18	ARP-024	ARP-029
20	ARP-026	ARP-030
22	ARP-028	ARP-031
24	ARP-029	ARP-032

Conversion Table

Salt Water Depth to Hydrostatic Pressure

Salt-Water Depth in Feet	Pounds per sq. inch	Salt-Water Depth in Feet	Pounds per sq. inch
10	4	2,000	890
25	11	2,500	1,113
50	22	3,000	1,335
75	33	4,000	1,780
100	45	5,000	2,225
200	89	6,000	2,670
250	111	7,000	3,115
300	134	7,500	3,338
400	178	8,000	3,560
500	223	9,000	4,005
600	267	10,000	4,450
750	334	15,000	6,675
800	356	20,000	8,900
1,000	445	25,000	11,125

Application Tooling

Contact Size	Crimping Tool	Positioner	Insertion Tool*	Removal Tool*	Sealing Plug*	Color Code	Reference Publication
22M	M22520/2-01	M22520/2-09†	11-8674-24	11-8675-24	10-405996-22	Black	L-624
22D	M22520/2-01	M22520/2-09†	11-8674-24	11-8675-24	10-405996-22	Black	
22	M22520/2-01	M22520/2-09†	11-8674-22	11-8675-22	10-405996-22	Black	
20	M22520/1-01	M22520/1-04	11-8674-20	11-8675-20	10-405996-20	Red	
16	M22520/1-01	M22520/1-04	11-8674-16	11-8675-16	10-405996-16	Blue	
12	M22520/1-01	M22520/1-04	11-8674-12	11-8675-12	10-405996-12	Yellow	

* Amphenol Part Numbers

† Pin only, use M22520/2-06 for socket contacts